





## Sirocco 2-M 6x 100W LED






60,000 Lm on a  
1kVA Generator

Hot restrike

Multi-lamps





### ▶ TECHNICAL DATA

Lamps	6x 100w LED
Average lamps life*	50,000 hours
Max Lumen	100 lm/W
Type of Lamp Socket	6 x Blocks [ Driver + LED ] independent Fast and easy to replace (4 screws)
Maximum power	600 W
Available voltages	110~220v / 50 Hz
Restrike time	Instant
Main power supply or 1kVA generator	
Envelope diameter	3 ft
Envelope height	2 ft
Envelope options:	multiple envelope colors, without reflector, reverse reflector

\* Under normal conditions of use

### ▶ LIGHTING DATA

Open core area lighting requirement (EN1838 norm)	18,200 sq/ft
Very low risk area lighting requirement for safety and security (EN12464-2 norm)	10,200 sq/ft
Light under the balloon (10 ft)	46.5 fc
Maximum lumen	60,000 lm
Color temperature: DAYLIGHT	6,000°K

### ▶ SAFETY

Flame-retardant fabric	
Silver reflector to improve illumination under balloon and avoid light pollution	
Rain and dust proof material	IP54
Maximum ambient temperature	115°F
Integrated fuse protection + breaker and pressure sensor	
Wind Resistance	62 mph

### ▶ PACKAGE INCLUDES

Full set lighting balloon with 6 LEDs, repair patch kit, user manual, 1 glove in a black PVC cylinder case